

In producing epoxy mastic, Polymeric Systems, Inc in the USA cut batching time from three to one-and-a-half hours by switching from manual dumping of 28 kg bags of dry inorganic powder to automated weigh batching directly from bulk bags. The system contained dust and reduced potential injuries related to manual lifting and emptying of bags.

Operators previously dumped 28 kg sacks of dry inorganic powder, up to 32 bags per batch, into a 950 litre kneader-extruder or one of two 380 litre kneader-extruders. Today, three Flexicon bulk bag dischargers, each equipped with an 226 litre capacity receiving hopper and 3-4,5 m long, 11,4 cm diameter flexible screw conveyor, unload powder from 1 135 kg) bulk bags as the flexible screw conveyors convey the material in pre-selected batch weights to any of three kneader-extruders under loss-of-weight control.

**Batch weights,
recipes set in 60 seconds**

Because sack weights fluctuated by up to 2,25 kg, operators weighed each sack and adjusted for variations. Now, adjusting a batch weight, or selecting one of Polymeric's nine epoxy mastic recipes, requires a one-minute entry on the control panel. The operator is freed for other tasks rather than being tied to the batching process. The only manual task involves adding small amounts of minor fillers from 28 kg bags into the hopper, which is equipped with a bag tray support and hinged cover.

**Weigh batching system
accurate to $\pm 0,12\%$**

A control panel entry initiates unloading of the bulk bag and conveying of powder in precisely weighed batches to the kneader-extruder. As a bag empties, load cells supporting the discharger frame transmit weight-loss signals to the controller which steps down the conveyor to a dribble feed rate immediately prior to stopping the conveyor once the accurate batch weight has been unloaded. Batches between 180-720 kg are accurate to 0,9 kg.

**Flow promotion devices move
stubborn powder**

Flow promotion devices integral to the bulk bag discharger frame promote a continuous flow of material into and through the bag discharge spout. A manual Spout-Lock™ clamp ring mounted atop a Tele-Tube™ telescoping tube creates a sealed connection between the clean side of the bag outlet spout and the clean side of the telescoping tube.

AUTOMATED POWDER UNLOADING HALVES BATCHING TIME



One of three bulk bag weigh batch unloading systems equipped with 226 litre capacity receiving hoppers and 114 mm diameter flexible screw conveyors, discharges powder from 1 135 kg bulk bags, transporting it under loss-of-weight control to any of three kneader-extruders. A bag tray support and hinged hopper cover allow manual additions of minor ingredients.



Problem-free bulk handling

(even with problematic materials)



Components range from Multiple Discharge Conveyors, Bulk Bag Dischargers/Fillers, Bag Dump Stations, Drum Dumpers and Weigh Batching Sub-systems to Blenders, Screeners, and other mechanical process equipment—all interconnected by Flexicon conveyors—all available in industrial, food, or pharmaceutical finishes.

Whether your materials are difficult or easy to handle, you can enjoy the simplicity, reliability and economy of an automated bulk handling system from Flexicon®—because it can load, unload, weigh batch, blend, feed, screen, convey and process a diversity of materials that other bulk handling systems simply cannot.

Flexicon can custom-engineer and integrate components or automated systems into your new or existing process, and best of all, assume complete responsibility for system support, and guarantee your results. Problematic bulk materials or not.

FLEXICON AFRICA (PTY) LTD.
P.O. Box 10450
Linton Grange
Port Elizabeth, South Africa 6015
Tel: +27 41 453 1871
Fax: +27 41 453 1670
E-mail: sales@flexicon.co.za

USA
1 610 814 2400

FRANCE
+33 (0)3 23 40 11 05

UNITED KINGDOM
+44 (0)1227 374710

AUSTRALIA
(+61 3) 9335 4134

NEW ZEALAND
(+64 9) 576 7013

www.flexicon.com

flexicon®



©2002 Flexicon Corporation. Flexicon Corporation has registrations and pending applications for the trademark FLEXICON throughout the world.

As the bag empties and elongates, the telescoping tube keeps the spout taut at all times by maintaining constant downward tension, preventing excess spout material from bulging outward (creating dead pockets) or falling inward (creating flow restrictions).

Flow-Flexer™ bag activators raise and lower opposite bottom edges of the bulk bag at timed intervals, promoting material flow into the bag discharge spout. As the bag lightens, the stroke of the bag activators increases, raising the bag into a steep 'V' shape for total evacuation of material.

A pneumatic turbine vibrator in the hopper promotes the flow of powder into the flexible screw conveyor's charging adapter.

For leak-proof retying of partially empty bags, a Power-Cincher™ flow control valve employs a series of curved, articulated stainless steel rods that cinch the spout concentrically on a horizontal axis and vertically in a tight zig-zag pattern, preventing leakage of the finest powders.

Dust-tight system prevents contamination

The dry inorganic powder remains fully enclosed as it travels throughout the sealed system of interconnected equipment consisting of the bulk bag discharger, hopper, flexible screw conveyor and kneader-extruder, preventing contamination of the product and plant environment. Previous bag dumping in open air created dust and allowed paper scraps to enter the batch.

Each flexible screw conveyor consists of a durable plastic outer tube enclosing a model 1450 conveyor spiral, specially designed to accommodate the highly aeratable inorganic powder. Flexicon applications engineers also incorporated several design elements to overcome the challenges associated with handling the powder.

John Kimmich, plant manager, commented: "The system enables us to switch to different products rapidly, meeting the needs of customers in the OEM, do-it-yourself and retail markets." He expects the system to pay back in less than two years from the labour savings and productivity gains.

In addition to bulk bag dischargers and flexible screw conveyors, Flexicon manufactures pneumatic conveying systems, bulk bag fillers, manual dumping stations, drum dumpers, weigh batching and blending systems and plant-wide bulk handling systems with automated controls.

Article supplied by Flexicon Africa. For information telephone +27 41 453 1871 or email sales@flexicon.co.za.

