

A U S T R A L I A N

# BULK HANDLING


R E V I E W

[www.bulkhandling.com.au](http://www.bulkhandling.com.au)

Volume 14 No 2

March/April 2009

- Profile of Emeritus Professor Alan Roberts
- Major ports turn to Tasman-Warajay for coal transfers
- Technical paper: Design fundamentals for drive systems on conveyors
- Almondco installs Cablevey conveyors
- 4th Australian Bulk Handling Awards
- BULKEX: provisional CHoPS agenda and UK industry profile



 **Tasman**  
WARAJAY  
A **FLEXCO** Company

# Food plant installs Flexicon discharger

A UK food processor installed a dust-tight bulk bag discharger with flexible screw conveyor, from Flexicon. The system eliminated waste, and improved safety and quality.

To compete internationally, Danisco A/S, a multinational ingredient manufacturer with operations in 147 locations in 47 countries, constantly reviews its processing operations with a view to trimming costs for its customers.

An inefficient production system at the company's food-ingredient plant in Beaminster, Dorset, for nisin, a natural antimicrobial food preservative and shelf-life extender used in cream cheese, liquid egg and many other foods, prodded managers to rethink their system. They needed to streamline flow and reduce material handling to eliminate waste and cut manpower costs.

With world food markets increasingly price-sensitive, Danisco's customers demand cost efficiency from suppliers. Even small inefficiencies can mean the difference between staying competitive and losing a market, and since Beaminster is Danisco's only nisin production plant, making the operation as efficient as possible was critical.

The system had 25kg bags of raw materials forklifted from storage and stacked next to an elevator, which raised the bags to a platform three metres above the plant floor. An automatic bag splitter cut open each bag, and a worker emptied the contents into a hopper that gravity-fed the material onto an open conveyor toward processing.

material left in every bag either would be spilled on the platform, requiring additional clean-up, or simply disposed of with the bag.

Plant management estimated that about 100g per bag was lost, totaling about 80kg of lost material per week. The platform and elevator also required regular maintenance.

***Since Beaminster is Danisco's only nisin production plant, making the operation as efficient as possible was critical.***

Empty bags accumulated quickly, and a worker had to regularly climb the platform to gather and bunch them for disposal. Moreover, after the bags were sliced open, despite thorough shaking by an operator, the bags were never fully emptied. The small amount of residual

## Go with the flow

As a solution, Danisco installed a Flexicon bulk bag discharging system that conserves plant floor space and reduces costs, waste and dust while improving plant hygiene along with worker health and safety.



*The new bulk bag discharger system at Danisco covers a small footprint while reducing costs and waste.*



*The new bulk solids handling system has contained dust and reduced injuries related to manual bag handling.*

Prior to designing the system, Flexicon Europe lab tested the flow characteristics of each raw material Danisco handles. The materials were found to be hygroscopic, so protecting them from airborne moisture was important. But they were also free flowing, so no mechanical flow assistance was needed. The ingredients were also found to possess similar angles of repose - about 30-45 degrees - which helped determine the hopper wall angles necessary for efficient flow.

With this information in hand, Flexicon Europe designed a bulk solids handling system that uses a bulk bag discharge frame featuring a cantilevered "I" beam from which the bulk bag gravity feeds ingredients into a receiving hopper that feeds a 4.5-metre flexible screw conveyor housed within a polymer tube.

A Bag-Vac dust collection system mounted on the side of the bulk bag frame collects 99.99 per cent of particles 5 microns or greater in size. The dust collector produces a vacuum to collapse empty bags prior to bag disconnection, eliminating the need for manual flattening and thus reducing the risk of the operator inhaling dust. All ingredient-contact parts are made from Type 316 stainless steel with a food-grade finish, meeting the plant's stringent requirements.

**Bulk efficiencies reduce costs**

The bulk-bag discharger frame enables Danisco to purchase ingredients cost effectively in bulk bags; the need for 25 kg bags is reduced by about 90 per cent,

with the smaller bags now used only for minor ingredients.

The forklift operator positions a bulk bag in front of the discharger frame and attaches it, via straps, to an electric hoist that lifts the bag above the receiving hopper. A Spout-Lock clamp ring positioned above a pneumatically activated Tele-Tube telescoping tube enables the operator to make a quick, dust-tight connection between the bag spout and hopper.



*The flexible screw conveyor moves the free-flowing raw material 4.5 metres at a 45-degree incline into a hopper.*

At the push of a button the telescoping tube raises the clamp ring assembly, allowing the bag spout to be pulled through the ring. The operator then lowers the clamp ring, sealing the clean side of the bag spout to the clean side of the telescoping tube. The bag's spout is then manually untied,

with the dust tight seal allowing full open discharge from the bag without risking particulate inhalation by the operator.

The telescoping tube assembly exerts continual downward tension on the spout, elongating the bag as it empties, thus promoting complete material discharge into the receiving hopper. A side-mounted hopper sensor informs the operator about the status of material flow.

From the receiving hopper, the free-flowing raw material gravity-feeds into the intake adapter of the flexible screw conveyor, which moves the material 4.5 metres at a 45-degree angle, then down through a discharge adapter that empties into the blender that begins downstream nisin production.

**Smaller, safer and QA-audited**

The new system occupies half the footprint of the old one. It significantly reduces manual bag handling and related injuries, while the dust-tight connections and Bag-Vac dust collector eliminate plant contamination. The bulk bag discharger system also promotes uniform ingredient flow and transfer, giving Danisco greater control over its nisin mixing, while reducing bag waste and ingredient costs.

Finally, the new system meets Danisco's internal and audited quality-assurance programs, which include health and safety, environment, quality and food safety (SHEQ), preferred supplier processes, hazard analysis critical control points (HACCP) and social responsibilities.

Contact: [sales@flexicon.com.au](mailto:sales@flexicon.com.au)

Head Office: 6 Wadmirer Drive  
Boronia VIC 3155 Australia  
Tel: (03) 9800 6777  
Fax: (03) 9800 2211



[www.enmin.com.au](http://www.enmin.com.au)



Enmin Pty Ltd Exclusive Agents for  
**COUGAR**  
INDUSTRIES, INC.



**Cougar Industries - The Leader in Industrial Vibration**

Cougar Industries Inc., patented the world's first 12 volt truck vibrator in 1964. With vibrators their only focus, Cougar has strived to ensure the Cougar name is synonymous with exceptional products, workmanship and service support.

Enmin are proud to be

recognized as the Asia Pacific agent for the entire range of Cougar industrial vibrators. With stock available in Australia, New Zealand, Malaysia and Thailand we are sure to be able to meet the most demanding requirements.

Experience has shown there is no easy fix solution,

likewise there is no one product to solve all material flow problems.

With over 25 years experience, we offer support that's second to none. Visit our web site today to view our product range or give us a call on (03) 9800 6777.